


3-1/2" Ø X 0.216 WALL. SERIES



- Capacity:** Up to 2,500 lbs. (See chart below)
- Minimum B.F.R.:** 4"
- Maximum B.F.R.:** 120" (Contact Sales if larger B.F.R. required)
- Bearings:** Replaceable
- Construction:** Press fit bearing retention
- Restrictions:** All B.F.R. s require a cottered axle

For more information on further roller options or to place an order, contact our Order Desk!

Steel Roller



a

TUBE

- | Code | Description |
|------|---|
| VQ | 3-1/2" Ø x 0.216 Wall Natural Finish (STD.) |
| VK | 3-1/2" Ø x 0.216 Wall Zinc Plated |

b

BEARING

- | Code | Description |
|------|-------------------------------------|
| 85 | Grease packed BG-85 (STD.) |
| 90 | Precision BG-90 c/w insert |
| 95 | Dust Resistant BG-95 c/w Shot Guard |

c

AXLE

- | Code | Description |
|------|--|
| QW | 1-1/16" Hex, Cottered, Natural Finish (STD.) |

d

BETWEEN FRAME RAIL (B.F.R.)

Measurement between the inside of the two frame rails
Eg. For a 14-1/4" B.F.R measurement, enter 014 250

B.F.R (inches)	4	9	15	21	27	33	39	45	51	57	63
Steel Roller Capacity	2500	2500	2500	2500	2500	2500	2500	2500	2446	2441	2233

B.F.R (inches)	69	75	81	87	93	99	105	111	117	120
Steel Roller Capacity	2022	1845	1694	1564	1451	1351	1262	1030	775	648

*interpolate for intermediate B.F.R's