


# 1-3/8' Ø X 14 GA. SERIES

- Capacity:** Up to 80 lbs. (See chart below)
- Minimum B.F.R.:** 4'
- Maximum B.F.R.:** 39' (Contact Sales if larger B.F.R. required.)
- Bearings:** Non-replaceable
- Construction:** Formed end bearing retention
- Restrictions:** Rollers under 7' B.F.R. require a cottered axle

For more information on further roller options or to place an order, contact our Order Desk!

## Steel Roller



**a**

### TUBE

Code	Description
1A	1-3/8" Ø x 14 Ga. Natural Finish (STD)
1F	1-3/8" Ø x 14 Ga. Zinc Plated 1-3/8" Ø
1L	x 14 Ga. Aluminum

**b**

### BEARING

Code	Description
10	Plain Ball BG-10 (STD.)

**c**

### AXLE

Code	Description
4N	5/16" Hex, Spring Loaded, Natural Finish (STD.)
4T	5/16" Hex, Cottered, Natural Finish
4Y	5/16" Hex, D+T 10-32 UNF, Natural Finish
5D	5/16" Hex, Spring Loaded, Zinc Plated
5J	5/16" Hex, Cottered, Zinc Plated
5P	5/16" Hex, D+T 10-32 UNF, Zinc Plated

**d**

### BETWEEN FRAME RAIL (B.F.R.)

Measurement between the inside of the two frame rails  
Eg. For a 14-1/41B.F.R measurement, enter 014 250

B.F.R (inches)	4	9	12	15	18	21	24	27	30	33	36	39
Steel Roller Capacity	80	80	80	80	80	80	80	80	80	80	80	80

\*interpolate for intermediate B.F.R's