


# 2-1/2" Ø X 14 GA. SERIES



- Capacity:** Up to 310 lbs. (See chart below)
- Minimum B.F.R.:** 5"
- Maximum B.F.R.:** 60" (Contact Sales if larger B.F.R. required)
- Bearings:** Replaceable
- Construction:** Formed end housing retention c/w press fit bearing
- Restrictions:** Rollers under 7" B.F.R. require a cottered axle.

For more information on further roller options or to place an order, contact our Order Desk!

## Steel Roller



**a**

### TUBE

Code	Description
KA	2-1/2" Ø x 14 Ga. Natural Finish (STD.)
KF	2-1/2" Ø x 14 Ga. Zinc Plated

**b**

### BEARING

Code	Description
50	Grease packed c/w housing BG-50 (STD.)
55	High Speed & Quiet c/w housing BG-55

**c**

### AXLE

Code	Description
8W	7/16" Hex, Spring Loaded, Natural Finish (STD.)
gB	7/16" Hex, Cottered, Natural Finish
gG	7/16" Hex, D+T 5/16-18 UNC, Natural Finish
gM	7/16" Hex, Spring Loaded, Zinc Plated
gS	7/16" Hex, Cottered, Zinc Plated
gX	7/16" Hex, D+T 5/16-18 UNC, Zinc Plated

**d**

### BETWEEN FRAME RAIL (B.F.R.)

Measurement between the inside of the two frame rails  
Eg. For a 14-1/4" B.F.R measurement, enter 014 250

B.F.R (inches)	5	9	15	21	27	33	39	45	51	57	60
Steel Roller Capacity	310	310	310	310	262	211	175	149	129	113	106

\*interpolate for intermediate B.F.R's